

HEADERS FOR PCB.
CONNETTORI MASCHIO PER C.S.
CONNECTEURS MÂLE POUR C.I.
STIFTLISTE FÜR LEITERPLATTEN

Pitch / Passo	mm
Rated Voltage / Tensione nominale	V
Rated Current / Corrente nominale	A
Temperature / Temperatura	°C
Housing / Corpo isolante	PA - UL 94 V0

IMQ	EN61984
VDE	EN61984
cUL	UL1059 + C22 2 n°158

Poles / Poli	X
Colors / Colori	Y
Other information / Altre dati	P

MRT9	P3.5	X	SQ	Y	N...
Type / Tipo	Pitch / Passo	Poles / Poli	Version / Versione	Colors / Colori	Marking / Marcatura

Version / Versione	SQ*
Version / Versione	SQ*


* SQ Version = Horizontal version

MRT9

Single block - Blocco unico
 Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/20





3,5 - 3,81
200
12

110
PA - UL 94 V0

V	A	mm ² /AWG
150	12	0,2 ÷ 1,0
300	8	30 ÷ 16

min 2 - max 20
VE / on demand GR GR NE AR BL RO GI
D/B4




MRT9..SQ*

Single block - Blocco unico
 Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/20





3,5 - 3,81
200
12

110
PA - UL 94 V0

V	A	mm ² /AWG
150	12	0,2 ÷ 1,0
300	8	30 ÷ 16

min 2 - max 20
VE / on demand GR GR NE AR BL RO GI
D/B4



MRT9

Single block - Blocco unico
 Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/10





7 - 7,62
400 - 500
12

110
PA - UL 94 V0

V	A	mm ² /AWG
400 (7)	500 (7,62)	12
300	8	30 ÷ 16

min 2 - max 10
VE / on demand GR GR NE AR BL RO GI
D/B4




MRT9..SQ*

Single block - Blocco unico
 Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/10





7 - 7,62
400 - 500
12

110
PA - UL 94 V0

V	A	mm ² /AWG
400 (7)	500 (7,62)	12
300	8	30 ÷ 16

min 2 - max 10
VE / on demand GR GR NE AR BL RO GI
D/B4




MRT9..FV

Single block - Blocco unico
 Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/10





7 - 7,62
400 - 500
12

110
PA - UL 94 V0

V	A	mm ² /AWG
400 (7)	500 (7,62)	12
300	8	30 ÷ 16

min 2 - max 10
VE / on demand GR GR NE AR BL RO GI
D/B4




MRT33

Single block - Blocco unico
 Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/12



3,81
200
10

110
PA - UL 94 V0

V	A	mm ² /AWG
300	8	30 ÷ 16

min 2 - max 12
VE
D/B4

